

• ELECTRICAL • MECHANICAL • PNEUMATICS • HYDRAULICS

EMPH Engineering Solutions Grand Prix Mast Jack Range.

Crafted from aerospace-grade aluminum, these cylinders exemplify lightweight design and unparalleled durability. Our standard selection encompasses capacities ranging from 5 to 30 Tons. However, we also offer the flexibility to cater to individual requirements. Our adept team can manufacture custom-sized jacks, accommodating loads of up to 90 Tons, in direct response to customer needs.

Model No	Jack Type	Tons @ 350 bar	Tons @ 700 Bar	Stroke mm	Barrel Ø	Bore Ø	Rod Ø	Mtg: Body Thread Options	Collapsed Height*	Extended Height*	Port	Mass
	Internal -							M47 x 1.5 or as reqd by			1/4"-	
IJ5/700/75	Aluminium	2.5 Tons	5 Tons	75 mm	45 mm	30 mm	26 mm	client	183 mm	258 mm	18NPT	0.66 kg
	Internal -							M64 x 1.5 or as reqd by			1/4"-	
IJ10/700/75	Aluminium	5.5 Tons	11 Tons	100 mm	62 mm	45 mm	38 mm	client	230 mm	330 mm	18NPT	1.68 kg
	Internal -							M76 x 1.5 or as reqd by			3/8"-	
IJ15/700/100	Aluminium	7.5 Tons	15 Tons	100 mm	74 mm	52 mm	44 mm	client	243 mm	343 mm	18NPT	2.55 kg
	Internal -							M90 x 3 or as reqd by			3/8"-	
IJ20/700/100	Aluminium	10 Tons	20 Tons	100 mm	86 mm	60 mm	50 mm	client	264.5 mm	364.5 mm	18NPT	3.9 kg
	Internal -							M96 x 1.5 or as reqd by			3/8"-	
IJ25/700/100	Aluminium	12.5 Tons	25 Tons	100 mm	94 mm	65 mm	56mm	client	264.5 mm	364.5 mm	18NPT	4.65 kg
	Internal -				107			M110 x 2 or as reqd by			3/8"-	
IJ30/700/100	Aluminium	15.5 Tons	31 Tons	100 mm	mm	75 mm	65 mm	client	258.5 mm	358.5 mm	18NPT	5.74 kg
	Internal -				107			M110 x 2 or as reqd by			3/8"-	
IJ30/700/150	Aluminium	15.5 Tons	31 Tons	150 mm	mm	75 mm	65 mm	client	308.5 mm	318.5 mm	18NPT	6.84 kg

Notes:

Height* includes swivel shoe.

Port orientation, size and thread type can be changed to suit customer requirements.

Jack body mounting thread type and length can be changed to suit customer requirements.

Customer to check the length of body mounting thread required into the strength of the cylinder mounting material.

Strokes shown are standard. Custom strokes are available on request.

Standard Material is Hi-Strength Aluminium, hard coated to a dark bronze colour. Other materials are available on request.

All jacks are gravity return. Spring return available on request.